

Taper Sets



CRL TAPER-LOC® Taper Set for Monolithic Toughened Glass

CRL's TAPER-LOC® Taper Set for 12 to 19mm glass is made up of two Tapers and one L-Setting Block. Tapers are made of high strength reinforced nylon. They expand in thickness when compressed together with the Cat. No. TLK9/TLK12 Installation/Removal Tool, mechanically locking the glass panel into the base shoe. Not designed for Laminated Glazing.



CAT NO.	Description	Application
TL5X10	For 12, 15 and 19mm monolithic toughened glass For use with CRL's B5S, B5A, B5T, B6S and B7S glass balustrade base shoes	Great for glass balustrade and windscreen applications

NOTE: Minimum order: 10 sets.

CRL TAPER-LOC® Taper Set for Laminated Toughened Glass

Great for stadiums, apartments and shopping centres, or any areas trying to avoid the hazard of broken glass falling to lower levels. CRL's TAPER-LOC® Laminated Taper Set is made up of four Tapers and one L-Setting Block. Tapers are made of high strength reinforced nylon. They expand in thickness when compressed together with the Cat. No. TLK9/TLK12 Installation/Removal Tool, mechanically locking the glass panel into the base shoe.



CAT NO.	Description	Application
LTL10X	LTL10X designed for 21.52mm laminated toughened glass (10mm x 1.52mm x 10mm) and 25.52mm laminated toughened glass (12mm x 1.52mm x 12mm)	For use with CRL's laminated toughened glass balustrade base shoes only
LTL96X	LTL96X designed for 13.52mm laminated toughened glass (6mm x 1.52mm x 6mm) and 17.52mm laminated toughened glass (8mm x 1.52mm x 8mm)	For use with CRL's laminated toughened glass balustrade base shoes only

NOTE: Minimum order: 10 sets.

CRL TAPER-LOC® Taper Set for Monolithic Toughened Glass (Windscreens Only)

CRL's TAPER-LOC® Taper Set for 10mm glass is made up of two Tapers and one L-Setting Block. Tapers are made of high strength reinforced nylon. They expand in thickness when compressed together with the Cat. No. TLK9/TLK12 Installation/Removal Tool, mechanically locking the glass panel into the base shoe. Not designed for Balustrade Applications or Laminated Glazing.



CAT NO.	Description	Application
TL3W10	For 10mm monolithic toughened glass 914mm recommended maximum glass height	Great for glass windscreen applications Not suitable for balustrade applications

NOTE: Minimum order: 10 sets.